

GC6910 MD3 // HD3

**DIRECT-DRIVE HIGH-SPEED LOCKSTITCH SEWING MACHINE WITH DROP FEED
& INTEGRATED MOTOR CONTROL UNIT**

**DOPPELSTAPPSTICH-SCHNELLNÄHER MIT DIREKTANTRIEB UND UNTERTRANSPORT
& INTEGRIERTER STEUERUNG**



TYPICAL

EN Technical Data

- Stitch type 301
- Max. sewing speed 5.000 spm. **(MD3)**
- Max. stitch length 7 mm **(HD3)**
- Max. fabric clearance 13 mm (with knee lever)
- Integrated direct-drive (300 Watt) for extreme smooth and vibration-free running **(MD3)**
- Motor control unit integrated in machine belt cover, so it's easier and faster to build up a machine
- Push button on machine head for half-stitch function, integrated sewing light & back tack
- Reduction of energy consumption

Clearance under the arm

260×130 mm

Automatic oil pump lubrication system

Friction bearing bedded arm shaft

Models

- **GC6910 MD3** | Standard fast seamer for light to medium materials; Standard hook size; with direct-drive, automatic thread cutter, thread wiper & automatic back tack & motor control on sewing head
- **GC6910 HD3** | Standard fast seamer for medium to heavy materials; Standard hook size; automatic back tack & motor control on sewing head

Carton dimensions & gross weights for sewing head

66×32×47 cm, 42 kg

° Options

Automatic presser foot lifter

Specifications can differ depending on model.

DE Technische Daten

- Stichtyp 301
- Max. Nähgeschwindigkeit 5.000 Stiche / Min. **(MD3)**
- Max. Stichlänge 7 mm **(HD3)**
- Max. Durchgang unter dem Nähfuß 13 mm (mit Kniehebel)
- 300 Watt Direktantrieb für einen extrem ruhigen & vibrationsarmen Lauf **(MD3)**
- Steuerung in der Riemenschutzabdeckung integriert, dadurch Zeitersparnis beim Montieren der Komplettmaschine
- Taster am Maschinenkopf für Halbstichfunktion, integriertes Nählicht & Verriegelung
- Reduzierter Energieverbrauch

Durchgangsraum im Nähmaschinenarm

260×130 mm

Automatisches Druckumlauf-Schmiersystem

Gleitgelagerte Armwelle

Models

- **GC6910 MD3** | Standard-Schnellnäher für mittlere bis schwere Faden und Materialstärken; Standard-Greifergröße; automatische Verriegelungseinrichtung & Steuerung am Oberteil
- **GC6910 HD3** | Standard-Schnellnäher für mittlere bis schwere Faden und Materialstärken; Standard-Greifergröße & Steuerung am Oberteil

Kartonmaße & Brutto-Gewichte für Nähkopf

66×32×47 cm, 42 kg

° Optionen

Automatische Nähfußlüftung

Angaben können je nach Ausführung abweichen.



GC 6910	Model	Stitch Type	Max. Sewing Speed (spm)	Max. Fabric Clearance (mm)	Max. Stitch Length (mm)	Needle System	Needle Size	Thread Wiper	Automatic Back Tack	Pressure Foot Lifter	Thread Wiper	Thread Cutter	Sewing Light	LMH	
															Options
GC 6910	MD3	•	5.000	•	4.0	134/DP×5 70-110	31	•	•	•	•	•	•	•	L/M
	HD3	•	4.000	•	7.0	134/DP×5 110-140	35	•	•	•	•	•	•	•	H



XI'AN TYPICAL EUROPE GmbH

Hertelsbrunnenring 9
D-67657 Kaiserslautern
Tel.: +49 (0)631 316019-0
Fax: +49 (0)631 316019-11

E-mail: sales@typical-europe.com
www.typical-europe.com

